

MIAMI-DADE COUNTY, FLORIDA METRO-DADE FLAGLER BUILDING 140 WEST FLAGLER STREET, SUITE 1603 MIAMI, FLORIDA 33130-1563 (305) 375-2901 FAX (305) 375-2908

NOTICE OF ACCEPTANCE (NOA)

Rotan Mahogany Millwork, Inc. 2525 SW 3rd Avenue Miami, Fl 33129

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed by Miami-Dade County Product Control Division and accepted by the Board of Rules and Appeals (BORA) to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Division (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. BORA reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Division that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the High Velocity Hurricane Zone of the Florida Building Code.

DESCRIPTION: Roatan Outswing Mahogany Door

APPROVAL DOCUMENT: Drawing No. 02-5522r1, titled "Mahogany Swing-Out Door", sheets 1 through 7, prepared, signed and sealed by Pedro De Figueiredo, P.E., dated 6/28/02, bearing the Miami-Dade County Product Control Approval stamp with the Notice of Acceptance number and approval date by the Miami-Dade County Product Control Division.

MISSILE IMPACT RATING: Large and Small Missile Impact

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA consists of this page 1 as well as approval document mentioned above.

The submitted documentation was reviewed by Theodore Berman, P.E.



NOA No 02-0510.04 Expiration Date: August 8, 2007 Approval Date: August 8, 2002 Page 1


DESIGNED PRESSURE RATING Pd= ± 75 PSF

MAXIMUM FRAME SIZES


FINISHED WIDTH: FW= 39 1/2" FINISHED HEIGHT: FH= 123"

MAXIMUM CLADDING SIZES

1/2" GLASLAM SAFETY-PLUS IMPACT GLASS
DLO: 25 3/4" X 103 1/2"
1 1/2" MAHOGANY SOLID WOOD PANEL
DLO: 25 3/4" X 103 1/2"




TYPE 1
SQUARE CONFIGURATION




TYPICAL SINGLE ELEVATIONS

TYPE 2
1/2 ARCH CONFIGURATION



TYPE 3
FULL ARCH CONFIGURATION



TYPE 4
LITE WITH SPLIT PANEL
CONFIGURATION

GENERAL NOTES:

1- DEFINITION: THIS PRODUCT IS A SWING-OUT MAHOGANY DOOR; DESIGNED, CONTRUCTED AND ERECTED TO ENCLOSE AN AREA, PROVIDING PROTECTION FROM HURRICANE FORCE WINDS WITHIN THE ALLOWABLE DESIGNED PRESSURES AND LIMITATIONS STATED IN THIS APPROVAL.

2- CODE: THIS PRODUCT HAS BEEN TESTED AND DESIGNED IN ACCORDANCE WITH THE 2001 FLORIDA BUILDING CODE, HIGH VELOCITY ZONES.

3- POSTING: A PERMANENT LEGIBLE DECAL SHALL BE PLACED AT A READILY VISIBLE LOCATION STATING THE FOLLOWING:

'ROATAN MAHOGANY MILLWORK INC - MIAMI - FLORIDA LARGE MISSILE IMPACT RESISTANT ROATAN SWING-OUT DOOR DADE COUNTY APPROVED'

4- LOADS: DESIGNED LOAD BASED ON THE ASCE 7-98. LOADS ARE TO BE PROVIDED BY A PROFESSIONAL ARCHITECT OR ENGINEER FOR EACH SPECIFIC PROJECT. THE CALCULATED DESIGNED PRESSURE MUST NOT EXCEED THE ALLOWABLE DESIGNED PRESSURE RATING.

5- MATERIAL: ALL WOOD MATERIAL TO BE FABRICATED FROM KILN DRIED MAHOGANY.

6- FASTENERS: ASSEMBLY SCREWS AND ANCHURS SHALL BE AS SPECIFIED IN THE CURRENT SET OF DRAWINGS. INSTALLATION AND LOADS AS PER THIS APPRIVAL.

7- USE: IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR, ARCHITECT OR ENGINEER OF RECORD TO VERIFY THE FOLLOWING:

7. 1- THE STABILITY OF THE STRUCTURE WHERE THE SHUTTER IS TO BE ATTACHED INSURING PROPER ANCHORAGE.

7. 2- THE SITE SPECIFIC PROJECT CRITERIA, SUCH AS BUT NOT LIMITED TO, WIND LOADS, LOCAL CODE REQUIREMENTS, DESIGNED PRESSURES ETC.
7. 3- THAT THIS APPROVAL IS ADEQUATE TO THE SPECIFIC PROJECT.

8- DISCLAIMER ENGCO INC. HAS NO CONTROL IN THE MANUFACTURING AND/OR PERFORMANCE OF THIS PRODUCT. THESE GENERIC PLANS WERE ENGINEERED IN ACCORDANCE WITH ACCEPTED ENGINEERING PRACTICES AND TEST DATA PROVIDED BY THE MANUFACTURER.

	BILL OF MATERIALS			
	ITEM#	DESCRIPTION	SIZE	REMARKS
	D1	BOTTOM RAIL	2, 25" X 10"	MAHDGANY WOOD
	D2	TOP RAIL & STILES	2. 25" X 4. 75"	MAHOGANY WOOD
	D3	EXTERIOR MOULDING	1. 50' X 1. 25'	MAHOGANY WOOD
	D4	INTERIOR MOULDING	1, 50° X 1, 375°	MAHOGANY WOOD
	D5	MID RAIL	2, 25° X 6, 25°	MAHOGANY WOOD
	GL1	IMPACT GLASS	1/2' ANNEAL	NOA #00-0524.06
	GL2	SOLID PANEL	1. 75" THICK	MAHOGANY WOOD
	F1	JAMB AND HEADER	1, 75" X6, 50"	MAHDGANY WOOD
	F2	SILL	1, 875 ' X6, 50 '	MAHDGANY WOOD
	G1	BOTTOM RAIL GASKET	2. 25° X0. 5°	PEMKO V80DS VINYL
	G2	FRAME SEAL	O. 65" XO. 58"	SCHEGEL QDS 650

Approved as complying with the Florida Baiding Code

Date AVOXA 8, 200 2

NOA! 20-05 (0-0)

Miami Dade Froduct Control

Division

Bucker Serv

MANUFACTURER:
Roatan
Mahogany
Millwork Inc

2525 SW 3rd Ave. Suite 210 MIAMI FLORIDA 33129 Tel.: (305) 858-0053

PRODUCT:
MAHOGANY
SWING-OUT
DOOR

Engineering: EngCo Inc.

CA 8116 6971 W. Sunrise Blvd. 104 Plantation, Fl. 33313 Tel.: (954) 585-0304



Date: 06/24/02 Scale: NA Design by: PPMF

Revision:

Drawing Number 02-522r1

Sheet 1 of 7


DESIGNED PRESSURE RATING Pd= ± 75 PSF

MAXIMUM FRAME SIZES

FINISHED WIDTH: FW= 75 1/2" FINISHED HEIGHT: FH= 123"


MAXIMUM CLADDING SIZES

1/2" GLASLAM SAFETY-PLUS IMPACT GLASS DLO: 25" X 103 3/4" 1 1/2" MAHOGANY SOLID WOOD PANEL DLO: 25" X 103 3/4"




TYPE 5
SPLIT PANEL CONFIGURATION

TYPICAL PAIR ELEVATIONS



TYPE 6
ARCH CONFIGURATION



TYPE 7
SQUARE CONFIGURATION

Approved as complying with the Florida Building Code
Date Augst 8 2062
NOAR 22-0510.04
Mismi Dade Product Control
Division Guerde By

MANUFACTURER:
Roatan
Mahogany
Millwork Inc

2525 SW 3rd Ave. Suite 210 MIAMI FLORIDA 33129 Tel.: (305) 858-0053

PRODUCT:
MAHOGANY
SWING-OUT
DOOR

Engineering: EngCo Inc.

CA 8116 6971 W. Sunrise Blvd. 104 Plantation, Fl. 33313 Tel.: (954) 585—0304




Engineer Seal Pedro De Figueiredo PE 52609

Date: 06/24/02 Scale: NA Design by: PPMF

Revision:

Drawing Number 02-522r1

Sheet 2 of 7



Mahogany Millwork Inc

MIAMI FLORIDA 33129 Tel.: (305) 858-0053

MAHOGANY SWING-OUT

EngCo Inc.

6971 W. Sunrise Blvd. 104 Plantation, Fl. 33313 Tel.: (954) 585-0304




Engineer Seal Pedro De Figueiredo


Date: 6/24/02 Scale: 1:1/4 & 3/8 Design by: PPMF


Drawing Number 02-522r1

Sheet of 7




NATIONAL .60" DIAM. THROW BOLT







ARDIMPEX THREE POINT **CREMONES**

SAME DETAIL TOP AND BOTTOM



HARDWARE LAY-OUT





* HARDWARE

- 1- 4 1/2"x 4 1/2"x .136 HAGER 1279 HINGES SPACED AS PER ELEVATIONS ABOVE AND CONNECTED WITH (8) #12x1 1/4" FH SMS. (SQUARE DOOR, 4 PER LEAF AND ARCH DOOR, 3 PER LEAF)
- 2- ARDIMPEX THREE POINT CREMONS ON ACTIVE LEAF FASTENED WITH (12) #10X 1 1/2" FH SMS.
- 3- HARROW PRODUCTS INC. FLUSH BOLTS 296G UL LISTED TOP AND BOTTOM OF INACTIVE LEAF.
- 4- SECONDARY LOCKS (ACTIVATE ONLY WHEN HURRICANE FORCE WINDS ARE EXPECTED) NATIONAL 0.60 DIA THROW BOLT ANCHORED WITH (6) #14X1 1/4" ON ACTIVE AND INACTIVE DOORS TOP AND BOTTOM RAILS.

MANUFACTURER: Roatan Mahogany Millwork Inc

2525 SW 3rd Ave. Suite 210 MIAMI FLORIDA 33129 Tel.: (305) 858-0053

PRODUCT: **MAHOGANY** SWING-OUT DOOR

Engineering: EngCo Inc.

CA 8116 6971 W. Sunrise Blvd. 104 Plantation, Fl. 33313 Tel.: (954) 585-0304



Date: 6/24/02 Scale: NA Design by: PPMF

PE 52609


Revision:

Drawing Number 02-522r1


> Sheet of 7

Approved as complying with the Florida Bulding Code


FRAMING ANCHORAGE DETAILS




OPTION 1 FRAME WITH MAXIMUM 1/4" PT WOOD SHIM 1/4" TAPCONS BY ELCO WITH 1 1/2" MIN. EMBEDMENT INTO 3320 PSI CONCRETE (SEE SHEET 3 OF 7 FOR ANCHORS LAY-OUT)



OPTION 2 FRAME WITH MAXIMUM 1/4" PT WOOD SHIM AND 1'X PT CONT. WOOD SPACER 1/4" TAPCONS BY ELCO WITH 1 1/2" MIN. EMBEDMENT INTO 3320 PSI CONCRETE (SEE SHEET 3 OF 7 FOR ANCHORS LAY-DUT)



FRAME WITH MAXIMUM 1/4" PT WOOD SHIM AND 2'X PT CONT. WOOD BUCK BY OTHERS #14 SS WOOD SCREWS WITH 1 1/2" MIN. EMBEDMENT INTO WOOD (SG=. 55) (SEE SHEET 3 OF 7 FOR ANCHORS LAY-DUT)



FRAME WITH MAXIMUM 1/4" PT WOOD SHIM 1/4'-20 HWH DRILFLEX SELF DRILLING SCREWS INTO MIN. 1/8" A36 STEEL (SEE SHEET 3 OF 7 FOR ANCHORS LAY-OUT)

TYPICAL DOOR CORNER

CONSTRUCTION

Approved as complying with the

Florida Buiding Code

Date NOR 8, 2007 NOA# 00-0510.04 Miami Dade Product Control

MANUFACTURER: Roatan Mahogany Millwork Inc

2525 SW 3rd Ave. Suite 210 MIAMI FLORIDA 33129 Tel.: (305) 858-0053

PRODUCT: **MAHOGANY** SWING-OUT DOOR

Engineering: EngCo Inc.

CA 8116 6971 W. Sunrise Blvd. 104 Plantation, Fl. 33313 Tel.: (954) 585-0304




Date: 6/24/02 Scale: NA

Design by: PPMF


Revision:

Drawing Number 02-522r1


Sheet of 7




ACTIVE ASTRAGAL INSTALLATION TO DOOR STILE SAME DETAIL TOP AND BOTTOM



INACTIVE ASTRAGAL INSTALLATION TO DOOR STILE SAME DETAIL TOP AND BOTTOM



TYPICAL CORNER FRAMING CONSTRUCTION




NOTE: AFTER FRAMING ASSEMBLAGE ALL JOINTS ARE TO BE SEALED WITH DOW 995 SILICONE.

FRAME AND DOOR ASSEMBLY


DOOR PARTS D2 STILES AND TOP RAIL BOTTOM RAIL --2,250--MADE OF THREE -2,250-MAHDGANY PLIES 750 10,000 D5 MID RAIL -MADE OF THREE -2,250-MAHDGANY PLIES 6.250 -MADE OF THREE MAHDGANY PLIES 1.250 -1.325-- 0.875 - 0.950 1.500 0,750 0.500 **D3 D4** EXTERIOR 0.570 0.620 INTERIOR MOULDING MOULDING

DOOR CLADDING

GL1- 1/2" GLASLAM SAFETY-PLUS LAMINATED CLEAR GLAZING MATERIAL NOA 00-0524, 06



GL2- 1 3/4" SOLID MAHDGANY PANEL



2.125-

1.000

D7 ACTIVE LEAF

ASTRAGAL

500

0.500 0.375

0.625

--1.500--

D6

INACTIVE LEAF

ASTRAGAL

2.250


1.250

0.500


2,375

1.125

FRAME PARTS




F1- JAMBS AND HEADER




F2- THRESHOLD

GASKETS



G1 RIGID VINYL BOTTOM RAIL GASKET PEMKO V80DS



QDS 650 SCHLEGEL WEATHERSTRIP

Approved as complying with the Florida Building Code
Date Avau 8, 2002
NOA# 02-0510-04
Miami Dade Product Control Division Glerden Gerra

MANUFACTURER: Roatan Mahogany Millwork Inc

2525 SW 3rd Ave. Suite MIAMI FLORIDA 33129 Tel.: (305) 858-0053

PRODUCT: **MAHOGANY** SWING-OUT DOOR

Engineering: EngCo Inc.

6971 W. Sunrise Blvd. 104 Plantation, Fl. 33313 Tel.: (954) 585-0304



JUN 2 8 2002

Engineer Seal Pedro De Figueiredo PE 52609

Date: 6/24/02 Scale: 1:1/2 Design by: PPMF

Revision:

Drawing Number 02-522r1

> Sheet 7 of 7